

Suitable for these applications and equipment



5 tine cultivator



0.8 m rotavator



1.5 ton trolley

Suitable for sugarcane, cotton and groundnut







Favourite will be double favourite from now



Extra pin in 3 point linkage for lower link mounting

To reduce lipping on soft soils.



Improved brake pedal position and additional foot block

Provide rest to work longer



Improved seat pan width
To provide comfort



32" (813mm) track width, 28" (711mm) track optional width

Gives better suitability for farming.



Better fender design



Improved reverse speed
Eliminates frequent gear changes.

Engine	
Cooling	Water Cooled
Fuel Tank Capacity (litres)	19
Transmission	
No. of gears	6 forward, 3 reverse
Maximum speed (km/h)	25
Break	Dry Disc break / OIB
Hydraulics	
Туре	Live, ADDC
Lift capacity at hitch point (kg)	778
Lower Link	Compatibility with CAT 1N
Tractor Description	
Tyre - Front	4.5 x 12, 6 (PR)
Tyre - Rear	8.00 x 18, 6 (PR)
Turning radius (m)	2.4



Aesthetic and new look



Toll Free No: 1800 425 6576 | www.mahindratractor.com 🚮 facebook.com/MahindraTractorsIndia

💟 twitter.com/TractorMahindra 🎟 📠 youtube.com/MahindraTractorsofficial 🎯 www.instagram.com/mahindratractorsofficial